

| | |
|---------------|-------|
| Project Name: | Type: |
| Part Number: | Date: |



GREENCREATIVE

DIRECT T8 VALUE SELECT

FEATURES

- Plug & Play – Easy to install
- Only compatible with Instant Start ballasts
- Replaces 32W T8 4' Fluorescent lamp
- Exceptional high efficacy up to 157LPW
- Opaque glass body reduces glare
- 310° extra wide light emitting area
- Suitable for use in enclosed fixture
- Meets NSF Requirements (use of a shatter guard required)
- UL damp location
- Temperature rating: -4°F/-20 °C- 95 °F/35 °C
- Rated lifetime (L70): 50,000hrs
- 5 years limited warranty
- Suitable for all indoor general lighting application



SPECIFICATIONS

| Product | Model | Equiv. | Input Voltage* | Wattage | Lumens | CCT | CRI | Efficacy (LPW) | Power Factor | THD | Beam Angle | Dim. | Fixture Rating | DLC |
|---------|----------------------|--------|----------------|---------|--------|-------|-----|----------------|--------------|------|------------|------|----------------|------|
| 98551 | 10.5T8/4F/830/IS/DIR | 32W | 120-277V | 10.5 | 1600 | 3000K | 82 | 152 | 0.9 | <20% | 160° | No | Enclosed | Apr. |
| 98552 | 10.5T8/4F/835/IS/DIR | 32W | 120-277V | 10.5 | 1600 | 3500K | 82 | 152 | 0.9 | <20% | 160° | No | Enclosed | Apr. |
| 98553 | 10.5T8/4F/840/IS/DIR | 32W | 120-277V | 10.5 | 1650 | 4000K | 82 | 157 | 0.9 | <20% | 160° | No | Enclosed | Apr. |
| 98554 | 10.5T8/4F/850/IS/DIR | 32W | 120-277V | 10.5 | 1650 | 5000K | 82 | 157 | 0.9 | <20% | 160° | No | Enclosed | Apr. |
| 98557 | 13T8/4F/840/IS/DIR | 32W | 120-277V | 13 | 2000 | 4000K | 82 | 154 | 0.9 | <20% | 160° | No | Enclosed | Apr. |
| 98558 | 13T8/4F/850/IS/DIR | 32W | 120-277V | 13 | 2000 | 5000K | 82 | 154 | 0.9 | <20% | 160° | No | Enclosed | Apr. |

* Ballast Dependent. Please refer to www.greencreative.com for full compatibility list

BALLAST PERFORMANCE


| Ballast Factor | Bare Lamp Wattage | System Wattage | 3000K Lumens | 3500K Lumens | 4000K Lumens | 5000K Lumens |
|------------------------------|-------------------|----------------|--------------|--------------|--------------|--------------|
| Low Ballast Factor (0.77) | 10.5 | 11 | 1250 | 1250 | 1300 | 1300 |
| Normal Ballast Factor (0.88) | 10.5 | 13 | 1600 | 1600 | 1650 | 1650 |
| High Ballast Factor (1.15) | 10.5 | 18.5 | 2100 | 2100 | 2150 | 2150 |
| Low Ballast Factor (0.77) | 13 | 13.8 | - | - | 1700 | 1700 |
| Normal Ballast Factor (0.88) | 13 | 16.5 | - | - | 2000 | 2000 |
| High Ballast Factor (1.15) | 13 | 23 | - | - | 2640 | 2640 |

Testing Method: Above system power is half the total system power of a 2-tube installation using an Instant Start ballast. Power and lumen output will vary based on ballast and fixture type. Above data is indicative only. Please visit www.greencreative.com for full ballast compatibility list



DIRECT T8 VALUE SELECT

DIMENSION & WEIGHT



| | |
|--------|--|
| Model | 13T8/4F/xxx/IS/DIR 10.5T8/4F/xxx/IS/DIR |
| Base | G13 |
| MOL | 47.76" (1213mm) |
| Dia. | 1.14" (29mm) |
| Weight | 0.67lb/304g |

Where xxx means 824-965 which indicates CRI and color temperature