

### **FEATURES**

- High output LED replacement for conventional 4FT fluorescent T8 lamps
- Ballast compatible, direct replacement LED tube (Type A)
- Simple "plug-and-play" solution, no fixture rewiring required
- 32W fluorescent equivalent replaces 4FT F32T8, F30T8, F28T8, and F28T8 tubes
- Internal coated glass tube no aging, no yellowing, no bending
- Environmentally friendly, no mercury
- Save up to 60% in energy compared to 32W fluorescent tubes
- Long life: rated for over 50,000 hours
- LED tubes last 3 to 5 times longer than fluorescents
- Suitable for dry and damp locations; open fixtures
- DLC 5.1, rebate eligible

### **APPLICATIONS**

- Office
- Classroom
- · Schools & Universities
- Hospital
- Retail
- Hospitality

### **CERTIFICATIONS**







## **BALLAST COMPATIBLE TLED LAMP**

# 4FT | 14 Watts | 2,200 Lumens | Type A

OEO's T8 LED tubes offer an energy-efficient, long-lasting alternative to traditional fluorescent lighting. Designed to fit standard fixtures, these ballast compatible tubes provide consistent brightness with significantly reduced power consumption. Ideal for both commercial and industrial use, our T8 LED tubes have a longer lifespan, reducing maintenance and replacement costs. Their flicker-free operation and instant-on feature ensure reliable performance. These T8's are ideal for office, school, warehouse, medical, & retail environments. Upgrade using OEO's T8 LED tubes for an eco-friendly lighting solution to enhance any space.



## **SPECIFICATIONS**

• TYPE: Type A - Ballast Compatible

• POWER: Existing electronic ballast

CCT: 3000K, 3500K, 4000K, 5000K, 6500K options

WATTAGE: 14WLUMENS: 2,200LM

• BEAM ANGLE: 210° distribution

BASE: G13 | medium bi-pin

CRI: 82

• EFFICACY: 157 lumens per watt

OPERATING TEMP: -4° to 113°F

• WARRANTY: 5 years / 50,000 hours

#### NOTE:

These Type A tubes only function with an operable electronic ballast. **Do not use in fixtures where the existing ballast has been removed or bypassed.** 




## **PRODUCT DETAILS**

Model	Length	Watts	Lumens	LPW	ССТ
OEO-LED-T8-4F-14W-2200LM-30K-BC	4FT	12W	2,200LM	157	3000K
OEO-LED-T8-4F-14W-2200LM-35K-BC	4FT	14W	2,200LM	157	3500K
OEO-LED-T8-4F-14W-2200LM-40K-BC	4FT	14W	2,200LM	157	4000K
OEO-LED-T8-4F-14W-2200LM-50K-BC	4FT	14W	2,200LM	157	5000K
OEO-LED-T8-4F-14W-2200LM-65K-BC	4FT	14W	2,200LM	157	6500K



### **DIMENSIONS**

Nominal Length: 48"



## **WIRING DIAGRAM**

