



FEATURES

- Retrofit your current HID fixture don't buy expensive new fixtures or worry about disposal fees
- Universal mounting hardware fits every fixture
- Converts vertical or horizontal mounted lamps
- Reduces energy and maintenance costs up to 80%
- Outstanding brightness, up to 148 lumens per watt
- Long lifespan: L70 lifetime > 200,000 hours
- Lightweight, more durable for mounting longevity
- Driver and mounting brackets included for both vertical and horizontal installation
- Replaces existing metal halide and HPS lamps in street lights, wall packs, canopies, high bay and low bay fixtures.
- DLC 5.1 rebate eligible

APPLICATIONS





Floodlight

Cobrahead

High Bay

Parking Lot

Garage / Canopy



CERTIFICATIONS



HID REPLACEMENT

OEO Green LED **Retrofit Kit**

OEO's Green LED Retrofit provides up to 80% reduction in energy consumption. It is designed to fit into your current HID fixtures via supplied mounting hardware, and makes a quick and easy way to upgrade to LED withought changing your existing fixtures. This is a perfect LED option if you have custom fixtures that are difficult or costly to replace. Suitable for both vertical and horizontal installation.



SPECIFICATIONS

- POWERED BY: 120-277V, 347-480V available
- ENERGY SAVINGS: Up to 80%
- COLOR TEMP: 5000K standard (4000K optional)
- BEAM ANGLE: 120° distribution
- **OPERATING TEMP:** -22°F to 113°F
- MOUNTING OPTIONS: "L" bracket for horizontal installation, "flat plate bracket" for vertical installation
- LED SOURCE: High output LEDs delivering up to 148 LPW
- FAN EQUIPPED: Sunon Brand
- DRIVER: Meanwell, UL, and cUL Approved
- HEAT SINK: Cold-forged pure aluminum
- HEAT CONDUCTIVITY: 2.4 times higher than die-castina
- CONTROLS: Optional photocell and motion sensor
- DIMMING: Dimmable 0-10V driver
- WARRANTY: 10 year LED, 5 Year driver







Wallpack

HID REPLACEMENT OEO Green LED Retrofit Kit

MOUNTING OPTIONS



BEFORE (shoebox fixture) ballast box and metal halide

ALL MOUNTING MATERIALS INCLUDED



AFTER (shoebox fixture) LED module, driver, L Bracket mount

PRODUCT SPECIFICATIONS

MODEL	REPLACES	LUMENS	LUMENS PER WATT	DIMENSIONS
GREEN RETRO G5 30W	75W-100W HID	4,050 LM	135	4.7" x 4.7" x 2"
GREEN RETRO G5 45W	100W-175W HID	6,100 LM	136	4.7" x 4.7" x 2"
GREEN RETRO G5 60W	150W-250W HID	8,100 LM	135	4.7" x 4.7" x 2"
GREEN RETRO G5 75W	175W-250W HID	10,195 LM	136	6" x 5" x 2"
GREEN RETRO G5 100W	250W-400W HID	14,205 LM	142	6" x 5" x 2"
GREEN RETRO G5 120W	400W-450W HID	16,200 LM	135	6" x 5" x 2"
GREEN RETRO G5 150W	450W-600W HID	20,250 LM	135	8" x 6" x 2"
GREEN RETRO G5 200W	600W-750W HID	27.926 LM	140	8" x 6" x 2"
GREEN RETRO G5 280W	750W-1000W HID	39,571 LM	141	10.6" x 10" x 3"
GREEN RETRO G5 320W	1000W HID	45,804 LM	143	10.6" x 10" x 3"
GREEN RETRO G5 350W	1000W-1500W HID	48,784 LM	139	10.6" x 10" x 3"

Notes: LPW information based on 5,000K, 4000K available upon request. 30W and 45W is only powered by 120-277V (no high voltage option).



OEO Green LED Retrofit Kit

L BRACKET AND PLATE INCLUDED WITH EVERY UNIT FOR MOUNTING TO ANY FIXTURE







HIGH-END COMPONENTS





