



FEATURES

- Outstanding brightness, 160 LPW, means more light output and less energy draw
- IP67: durable, tough construction for heavy duty applications
- Long life with low maintenance
- Lightweight, easy installation
- 90,000 hours rated LED life
- 5 year warranty
- Fast ROI payback
- Rebate eligible
- Multiple beam angles for best light distribution
- 30 day money back guarantee

APPLICATIONS

- Heavy Industrial Manufacturing
- Warehouse/Distribution Centers
- Paper and Textile Plants
- Steel and Iron Mills
- Airplane Hangars
- Water Treatment Plants

CERTIFICATIONS



OVERVIEW

Built to last, Apollo is IP67, a durable LED fixture with 160 lumens per watt, meaning more light and less energy used when compared to other fixtures. It distributes light specifically where needed and is totally resilient to dust and dirt, all while maintaining brightness and light uniformity.





PRODUCT SPECIFICATIONS

PRODUCT NAME	WATTAGES	REPLACES	LUMENS	DIMENSIONS	ССТ	CRI
OEO -AP-100						
	100W 2	50W-400W HID	16,000 Lm	12.6x12.6x7.9"	5000K	≥80



150W 400W HID 24,000 Lm 12.6x12.6x7.9" 5000K ≥80

MOUNTING OPTIONS









- Efficacy: 160 lumens per watt
- Powered By: 110V to 277V (347V-480V available)
- Energy Savings: 75+%
- Operating Temp: -22°F to 113°F
- Start-up: Instant on/off, instant restrike
- **Beam Angle:** 100W has 120° standard, 150W has 60° standard
- **Sensors:** Yes, optional and compatible
- Fixture Material: Aluminum Alloy
- Dimmable: Yes





BEFORE

ORDERING ex. OEO-AP-100W-ND-02-01-02

Brand OEO Model AP

Apollo LED High Bay Fixture Wattage

100W 100 watts 150W 150 watts Dimmability

ND Non Dimmable D

Dimmable

Optics

01

02 120° clear **03**

120° diffused

Mounting

01 Hanging Ring

02 Yoke Mount **Power Cable**

01

Power Cord (3ft)

02

Power Cord with Plug