

Save 70-80% with the OEO DIAMOND LED wall pack, a long-lasting solution that withstands extreme and demanding environmental conditions.



## FEATURES

- High brightness
- Sturdy aluminum alloy wall pack
- Stands up to extreme exterior environments
- 100,000 hours; L70
- 5 year warranty
- IP65 rating
- Maintains consistent performance
- Easy installation and reduced maintenance
- Rebate eligible, DLC
- Energy savings of 70-80%

## APPLICATIONS

- Exterior building perimeters
- Parking garages and stairwells
- Security lighting
- Doorway and pathway

## OVERVIEW

OEO's Diamond Wall Pack is a heavy duty, durable fixture, IP65 rating for wet and dirty outdoor environments. Improve the safety and security of your building, entry doors, dock areas and perimeter walkways.



BEFORE



AFTER

**PRODUCT SPECIFICATIONS**

| Model           | Replaces     | Lumen Output | Dimensions  | Weight |
|-----------------|--------------|--------------|-------------|--------|
| OEO Diam 45-AG  | 100-175W HID | 5,200        | 14" x 9.25" | 7 lbs  |
| OEO Diam 70-AG  | 150-250W HID | 8,000        | 14" x 9.25" | 7 lbs  |
| OEO Diam 90-AG  | 250-400W HID | 10,900       | 18" x 8.7"  | 9 lbs  |
| OEO Diam 135-AG | 400W HID     | 15,600       | 18" x 8.7"  | 10 lbs |

- Input voltage 100-277V
- 5000K; 80+ CRI
- 120° beam angle; bronze finish
- -40° F to 104° F operating temperature
- Waterproof wall pack

**CERTIFICATIONS**



**ORDERING**

ex. OEO-DM-60W-01-01-02-01

| DIAMOND       | POWER   | INPUT VOLTAGE              | COLOR TEMP  | SHADE OPTION                                       | PHOTOCELL OPTION                       |
|---------------|---|----------------------------|---|--|--|
| <b>OEO-DM</b> | <b>45W</b><br><b>70W</b><br><b>90W</b><br><b>135W</b> | <b>01</b> =<br>100-277V AC | <b>01</b> = 5,000K<br><b>02</b> = 4,000K<br><br>* 02 is special order | <b>01</b> = Regular<br><b>02</b> = w/ full cut-off | <b>01</b> = Photocell (swivel control) |

**NOTES**

- Photocell options available
- Semi-cutoff (full cut off by special order)
- Typical mounting height is 8-25 ft
- Typical spacing is 2 times the mounting height