



OVERVIEW

OEO's LED recessed troffer fixture delivers a superior replacement option for traditional fluorescent tube recessed troffer fixtures. Standard sizes of 2x2, and 2x4 are available to suit any office application and layout. This troffer light can be used for general office lighting, providing suitable light without any of the maintenance issues associated with fluorescent tubes. Installation is quick and simple when mounting into standard T-grid suspended ceiling systems. Constructed with a durable steel housing body and LED lifetime rating of at least 50,000 hours, this troffer is designed for many years of reliable operation.

FEATURES

- No UV or IR radiation
- Modern and efficient design
- Mercury-free construction
- Suitable for damp location use
- Easy and secure installation

APPLICATIONS

- Architectural decor
- Overhead task lighting
- Ambient room lighting
- Office lighting

CERTIFICATIONS



PRODUCT SPECIFICATIONS

MODEL:	OEO-2x2CD	OEO-2x4CD
Lumen Output	3600lm	4300lm
Luminous Efficacy	120 lm/W	120 lm/W
Beam Angle	100	100
Wattage	30 W	36 W
Input Voltage	120-277v	120-277v
CCT	4000K	4000K
CRI	>80	>80
Lifetime	50,000 hrs	50,000 hrs
Warranty	5 years	5 years
Dimmable	Yes (0-10v)	Yes (0-10V)
DLC	Yes	Yes
Dimensions	23.8"(L)x23.8"(W)x4.1"(H)	48.0"(L)x23.8"(W)x4.1"(H)