



FEATURES

- Economical LED
- Simply bypass ballast to retrofit your current high bay open fixtures; 120-277V direct
- Aluminum passive heat sink designed for dusty, dirty conditions
- Improved light output and better lumen maintenance than metal halide
- High efficiency output up to 120 lm/w
- 50,000 hours
- 5 year warranty
- DLC rebate eligible
- Fast ROI payback

APPLICATIONS

- Warehouse and Manufacturing Facilities
- Machine and Welding Shops
- Garages
- Metal Fabricators

CERTIFICATIONS



OVERVIEW

The OEO EZ LED ECO Series is designed to replace your HID bulbs, and is compatible with traditional HID fixtures. Simply replace your bulbs, wiring direct 110-277V, without disassembling the fixture. Get longer life using a fraction of the power.



BEFORE



AFTER

PRODUCT SPECIFICATIONS

PART NUMBER	REPLACES	WATTAGE	LUMENS	CCT	LUMENS PER WATT	CRI	DIMENSIONS
OEO-ECO-BB-P-75	175W HID	75W	9,000	5,000K	100	80+	7.48" x 10.82"
OEO-ECO-BB-P-120	250W HID	120W	13,000	5,000K	120	80+	9.06" x 12.05"
OEO-ECO-BB-P-160	400W HID	160W	20,000	5,000K	130	80+	11.03" x 12.2"

- **POWERED BY:** Wire direct 120-277V
- **ENERGY SAVINGS:** 60-70%
- **OPERATING TEMP:** -4°F to 122°F
- **START-UP:** Instant on/instant re-strike
- **DIMMING:** Non-dimmable



- Mogul E39/Ex39 base
- Easy installation; built-in LED driver
- Long neck for narrow domes
- Plastic overcast safer than metal
- Integrated aluminum heat sink ensures good heat dissipation
- Middle hole heat dissipation to speed up the flow of air
- Milky polycarbonate lens hides led chips

NOTES

- Turn off power when installing lamps
- Do not use with dimmers
- Open fixtures only
- Damp location rated
- Do not install in line voltage above 277V