

Save 70-80% with the OEO DIAMOND LED wall pack, a long-lasting solution that withstands extreme and demanding environmental conditions.



FEATURES

- High brightness
- Sturdy aluminum alloy wall pack
- Stands up to extreme exterior environments
- 50,000 hours; L70
- 5 year warranty
- IP65 rating
- Maintains consistent performance
- Easy installation and reduced maintenance
- Rebate eligible, DLC
- Energy savings of 70-80%

APPLICATIONS

- Exterior building perimeters
- Parking garages and stairwells
- Security lighting
- Doorway and pathway

OVERVIEW

OEO's Diamond Wall Pack is a heavy duty, durable fixture, IP65 rating for wet and dirty outdoor environments. Improve the safety and security of your building, entry doors, dock areas and perimeter walkways.



PRODUCT SPECIFICATIONS

Model	Replaces	Lumen Output	Dimensions	Weight
OEO JNT02-WPS-50	100-175W HID	6,000	14" x 9.25"	7 lbs
OEO JNT02-WPS-70	150-250W HID	8,400	14" x 9.25"	7 lbs
OEO JNT02-WPS-90	250-400W HID	10,800	18" x 8.7"	9 lbs
OEO JNT02-WPS-120	400W HID	14,400	18" x 8.7"	10 lbs

- Input voltage 100-277V
- 5000K; 75+ CRI
- 120° beam angle; bronze finish
- -40° F to 104° F operating temperature
- Waterproof wall pack

CERTIFICATIONS



ORDERING

ex. OEO JNT02-WPS-50W-01-01-02-01

MODEL	POWER	INPUT VOLTAGE	COLOR TEMP	SHADE OPTION	PHOTOCELL OPTION
OEO JNT02-WPS	50W 70W 90W 120W	01 = 100-277V AC	01 = 5,000K 02 = 4,000K * 02 is special order	01 = Regular 02 = w/ full cut-off	01 = Photocell

NOTES

- Photocell options available
- Semi-cutoff (full cut off by special order)
- Typical mounting height is 8-25 ft
- Typical spacing is 2 times the mounting height