

31919 - Ballast Bypass 4ft

LED15BT8/G4/835

- ☞ Existing fixture is wired to bypass the ballast.
- ☞ Fast and easy LED upgrade.
- ☞ Low energy LFL replacement.
- ☞ 66% longer life than LFL (50 000 vs. 30 000 hours).
- ☞ Better quality of light " instant on.
- ☞ Fully illuminates fixture - >270° light distribution.
- ☞ Easy disposal non-hazardous waste.
- ☞ Additional Cost Savings- ballast bypass wiring eliminates ballast replacement costs.
- ☞ For In-Line Fuse & Socket Kits please check our Awaken brochure.

PRODUCT PHOTO



GENERAL CHARACTERISTICS

Base Description	LED_Bs_G13
Base Type	G13
Dimmable	No
Product Technology	LED
Rated Life (Hours)	50000 h
Dimmable / Non-Dimmable	No
Lamp Count	1
Life in Years	45.7 yr
Requested Structure	Carton
Estimated Energy Cost per Year	1.81
Bulb Shape	T8

PHOTOMETRIC CHARACTERISTICS

Nominal Initial Lumen per Watt	137
Initial Lumens-nominal	2050 lm
Color Rendering Index-CRI	80
Color Temperature	3500 K

PRODUCT INFORMATION

Product Code	31919
Description	LED15BT8/G4/835
Alternative Unit Of Measure	CASE
Standard Package Quantity	20
Ean UPC	043168319195
Standard Package GTIN	10043168319192
No Of Items Per Sales Unit	
No Of Items Per Standard Package	20
Sales Unit	Case
UCC	
Alternative Unit Of Measure	EACH
Standard Package Quantity	1
Ean UPC	043168319195
Standard Package GTIN	00043168319195
No Of Items Per Sales Unit	
No Of Items Per Standard Package	1
Sales Unit	Each
UCC	

DIMENSIONS

Bulb Max Overall Length-MOL	48.0 in
-----------------------------	---------

ELECTRICAL CHARACTERISTICS

Voltage <Nom>	120 V
Rated power (Watts)	15 W