



## FEATURES

- 100,000 hour life L70
- Energy savings of 70%+
- IP66 rating: heavy duty fixture
- High brightness; 145 LPW
- Special optical design for precise aisle and rack lighting
- 5 year warranty
- Easy installation and reduced maintenance costs
- Rebate Eligible
- Extremely low glare

## APPLICATIONS

- Aisle and Bay Lighting
- Warehouse and Manufacturing Facilities
- Big Box Retailers
- Cold Storage Facilities

## CERTIFICATIONS



## OVERVIEW

The OEO Linear PRO is heavy duty and long lasting IP66 for wet and dirty environments. High brightness and selective beam-spread for your aisle layout. Get great energy savings and low maintenance over the long LED life ensuring consistent performance and fast ROI payback.



## PRODUCT SPECIFICATIONS

|   | Model           | Replaces     | Lumen Output | Dimensions          | Weight   |
|---|-----------------|--------------|--------------|---------------------|----------|
|  | Linear PRO 50W  | 175-250W HID | 7,000 lumen  | 13" x 4.1" x 3.8"   | 4.4 lbs  |
|  | Linear PRO 100W | 250-400W HID | 14,000 lumen | 24.5" x 4.1" x 3.8" | 7.1 lbs  |
|  | Linear PRO 150W | 400W HID     | 21,000 lumen | 36.1" x 4.1" x 3.8" | 10.4 lbs |
|  | Linear PRO 200W | 750W HID     | 28,000 lumen | 47.7" x 4.1" x 3.8" | 13.4 lbs |

- **OPTICS:** 5,000K; 70+ CRI
- **POWERED BY:** 100-277V (480VAC optional)
- **HUMIDITY:** 15-95% Relative Humidity
- **OPERATING TEMP:** -22°F to 122°F
- **BEAM ANGLE:** 60° x 100° (30° x 100°, 30°, 90°, 110°, 150° optional)
- **MOUNTING OPTIONS:** Chain or Surface Mount (3.2 ft cord standard)
- **DIMMING:** Optional

### DLC CODES

50W - PCMMRJT  
 100W - PW4TRWGG  
 150W - PTDWUJHX  
 200W - PQYZMA7G

## ORDERING

ex. OEO LIN-PRO-100W-01-01-01-03-02

| MODEL       | WATTAGE                     | INPUT VOLTAGE                  | COLOR TEMP                                | OPTICS   | DIMMABILITY  | MOUNTING                   |
|-------------|-----------------------------|--------------------------------|---|--|--|----------------------------|
| OEO LIN PRO | 50W<br>100W<br>150W<br>200W | 01 = 100-277V<br>02 = 347-480V | 01 = 5,000K<br>02 = 3,000K<br>03 = 4,000K | 01 = 60° x 100°<br>02 = 30° x 100°<br>03 = 30°<br>04 = 90°<br>05 = 110°<br>06 = 150° | 01 = Non-dimmable<br>02 = Microwave sensor dimmer<br>03 = Infrared sensor and dimmer<br>04 = Photocell | 01 = Chain<br>02 = Surface |